



NOTES:

1. VALVE SIZE: 350 MM (14 INCH).
2. PRESSURE RATE: PN 10.
3. VALVE BODY: FABRICATED CARBON STEEL,CAST IRON,CAST STEEL, STAINLESS,TITANIUM,NICKEL ALLOYS TO ASTM/IS STANDARD.
4. WEIGHT (APPROXIMATE): 275.5 LBS (125 KG).
5. HYDRAULIC ACTUATORS TO SUIT OUTPUT DRIVES IN ACCORDANCE WITH ISO 5211.
6. FLANGE DRILLING CAN ACCOMODATE BS 4504, DIN 2631/2/3/4 AS WELL AS ANSI B16.5, ANSI B16.47(A), API605(A), AWWA C207, IS 6392 AND IS 1538.



Advance Valves
142 A & B, Noida Special
Economic Zone, NOIDA,
Phase II - 201 305 (India)
Phone No: + 91 120 479 6900

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. Advance Valves makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

PN10-CL125-350

350 MM - DOUBLE OFFSET VALVE
SERIES BD LUG CLASS 125

| | |
|-------|----------|
| SCALE | NTS |
| UNIT | MM[INCH] |
| SHEET | 1 of 1 |